

TR 特轻负荷 LIGHTEST LOAD

| 尺寸 外径x内径x高度 ODxIDxLength mm | 刚度 Spring constant N/mm | 压缩量 Deflection mm | 负荷 Load N | 压并 Sold Heght mm |
|--------------------------------------|-------------------------------|-------------------------|-----------------|------------------------|
| TR14.5x920 | 11.77 | 10 | 107.9 | 8 |
| 25 | 9.41 | 12.5 | | 10 |
| 30 | 7.16 | 15 | | 12 |
| 35 | 6.18 | 17.5 | | 14 |
| 40 | 5.39 | 20 | | 16 |
| 45 | 4.81 | 22.5 | | 18 |
| 50 | 4.31 | 25 | | 20 |
| 55 | 3.92 | 27.5 | | 22 |
| 60 | 3.63 | 30 | | 24 |
| 65 | 3.33 | 32.5 | | 26 |
| 70 | 3.04 | 35 | | 28 |
| 75 | 2.84 | 37 | | 30 |
| 80 | 2.75 | 40 | | 32 |
| 90 | 2.35 | 45 | | 36 |
| 100 | 2.16 | 50 | 40 | |
| 125 | 1.77 | 62.5 | 50 | |
| TR17x11x25 | 15.69 | 12.5 | 186.3 | 10 |
| 30 | 12.45 | 15 | | 12 |
| 35 | 10.69 | 17.5 | | 14 |
| 40 | 9.32 | 20 | | 16 |
| 45 | 8.24 | 22.5 | | 18 |
| 50 | 7.06 | 25 | | 20 |
| 55 | 6.77 | 27.5 | | 22 |
| 60 | 5.88 | 30 | | 23 |
| 65 | 5.69 | 32.5 | | 26 |

银灰 SILVER-GREY

| 尺寸 外径x内径x高度 ODxIDxLength mm | 刚度 Spring constant N/mm | 压缩量 Deflection mm | 负荷 Load N | 压并 Sold Heght mm | |
|--------------------------------------|-------------------------------|-------------------------|-----------------|------------------------|----|
| TR26x16.5x65 | 12.36 | 32.5 | 402.1 | 26 | |
| 70 | 11.18 | 35 | | 28 | |
| 75 | 10.69 | 37.5 | | 30 | |
| 80 | 9.81 | 40 | | 32 | |
| 90 | 8.73 | 45 | | 35 | |
| 100 | 7.85 | 50 | | 38 | |
| 110 | 7.1 | 55 | | 43 | |
| 125 | 6.28 | 62.5 | | 49 | |
| 150 | 5.2 | 75 | | 58 | |
| 175 | 4.61 | 87.5 | | 70 | |
| 200 | 4.02 | 100 | | 80 | |
| TR32x21x40 | 30.89 | 20 | | 500.1 | 16 |
| 45 | 27.46 | 22.5 | | | 18 |
| 50 | 21.97 | 25 | | | 20 |
| 60 | 17.95 | 30 | 23 | | |
| 70 | 15.1 | 35 | 28 | | |
| 80 | 13.24 | 40 | 30 | | |
| 90 | 11.08 | 45 | 36 | | |
| 100 | 10 | 50 | 39 | | |
| 110 | 8.92 | 55 | 44 | | |
| 125 | 7.85 | 62.5 | 50 | | |
| 150 | 6.57 | 75 | 60 | | |
| 175 | 5.59 | 87 | 70 | | |
| 200 | 5 | 100 | 80 | | |
| 250 | 4.02 | 125 | 100 | | |

TR 特轻负荷 LIGHTTEST LOAD

银灰 SILVER-GREY

| 尺寸 外径x内径x高度 ODxIDxLength mm | 刚度 Spring constant N/mm | 压缩量 Deflection mm | 负荷 Load N | 压并 Sold Heght mm | 尺寸 外径x内径x高度 ODxIDxLength mm | 刚度 Spring constant N/mm | 压缩量 Deflection mm | 负荷 Load N | 压并 Sold Heght mm |
|--------------------------------------|-------------------------------|-------------------------|-----------------|------------------------|--------------------------------------|-------------------------------|-------------------------|-----------------|------------------------|
| TR17x11x70 | 5.3 | 35 | 205.9 | 28 | TR32x21x300 | 3.33 | 150 | 539.4 | 120 |
| 75 | 5 | 37.5 | | 30 | TR39x26x40 | 29.42 | 20 | | 15 |
| 80 | 4.71 | 40 | | 32 | 45 | 25.3 | 22.5 | | 18 |
| 90 | 4.12 | 45 | | 36 | 50 | 22.75 | 25 | | 19 |
| 100 | 3.73 | 50 | | 40 | 60 | 18.93 | 30 | | 21 |
| 125 | 2.94 | 62.5 | | 50 | 70 | 15.69 | 35 | | 23 |
| 150 | 2.45 | 75 | | 60 | 80 | 13.73 | 40 | | 26 |
| TR21x13x30 | 14.42 | 15 | | 12 | 90 | 11.96 | 45 | | 31 |
| 35 | 12.36 | 17.5 | | 14 | 100 | 10.79 | 50 | | 34 |
| 40 | 10.3 | 20 | | 16 | 110 | 9.81 | 55 | | 36 |
| 45 | 9.12 | 22.5 | | 18 | 125 | 8.63 | 62.5 | | 40 |
| 50 | 7.85 | 25 | | 20 | 150 | 7.16 | 75 | | 46 |
| 55 | 7.45 | 27.5 | | 22 | 175 | 6.18 | 87.5 | | 52 |
| 60 | 6.57 | 30 | | 23 | 200 | 5.39 | 100 | | 60 |
| 65 | 6.37 | 32.5 | | 26 | 250 | 4.31 | 125 | | 100 |
| 70 | 5.59 | 35 | | 27 | 300 | 2.63 | 150 | | 120 |
| 75 | 5.49 | 37.5 | | 30 | TR46x32x50 | 27.07 | 25 | | 18 |
| 80 | 4.9 | 40 | | 31 | 60 | 21.57 | 30 | | 20 |
| 90 | 4.31 | 45 | | 34 | 70 | 18.53 | 35 | | 24 |
| 100 | 3.92 | 50 | | 39 | 80 | 15.98 | 40 | | 26 |
| 125 | 3.33 | 62.5 | 50 | 90 | 14.12 | 45 | 29 | | |
| 150 | 2.75 | 75 | 60 | 100 | 12.75 | 50 | 31 | | |
| TR26x16.5x30 | 26.77 | 15 | 12 | 110 | 11.57 | 55 | 35 | | |
| 35 | 22.95 | 17.5 | 14 | 125 | 10.2 | 62.5 | 38 | | |
| 40 | 22.6 | 20 | 16 | 150 | 8.53 | 75 | 43 | | |
| 45 | 18.73 | 22.5 | 18 | 175 | 7.06 | 87.5 | 52 | | |
| 50 | 16.08 | 25 | 20 | 200 | 6.08 | 100 | 57 | | |
| 55 | 14.61 | 27.5 | 22 | 250 | 4.9 | 125 | 100 | | |
| 60 | 13.44 | 30 | 24 | 300 | 4.02 | 150 | 120 | | |
| | | | 402.1 | | | | | 608 | |